



COATED PRODUCTS DIVISION

## 50# Offset Linerless Label Material

### Preliminary Technical Specification


A self-wound white or canary yellow 50# offset paper coated with acrylic microsphere adhesive on one side and non-silicone release coating on the opposite side. Label material can be overprinted by flexco, inkjet and thermal transfer.

### Construction

Release Coating

50# White or Yellow Paper

Microsphere Adhesive



Paper Weight 81.0 grams/meter<sup>2</sup>

Paper Thickness 89.0 microns (µm)

### Adhesive Peel Force

(90° Angle, 12"/minute rate)

Stainless Steel, 10 minutes 1 ounce/inch

Stainless Steel, 24 hours 1.5 oz/inch

### Release Force Release from Itself

(90° Angle, 300"/minute rate) 2.0 oz/inch

As with any removable/repositionable adhesive labelstock, it is the responsibility of the user to test the adhesive against the intended surface for compatibility and functionality.

6761 Thompson Road North • Syracuse • New York • 13211

Toll Free U.S. 866.503.4273 • Telephone 315.634.3317 • Fax 315.437.3634

[www.cpdcoating.com](http://www.cpdcoating.com)



The mark of responsible forestry  
FSC Certification #BV-COC-070905  
© 1996 Forest Stewardship Council A.C.

CPD125 June2010